

EUROPEAN PATENT APPLICATION

Application number: 85308311.1

Int. Cl.⁴: A 61 M 16/00

Date of filing: 14.11.85

Priority: 30.11.84 JP 253495/84

Date of publication of application:
23.07.86 Bulletin 86/30

Designated Contracting States:
DE GB

Applicant: TOTTORI UNIVERSITY
101, Koyama-Cho-Minami 4-chome
Tottori City Tottori Prefecture(JP)

Inventor: Sato, Toru
2560 Hatagaaki
Yonago City Tottori Pref.(JP)

Inventor: Okazaki, Naoto
2725, Ryomitsuyanagi
Yonago City Tottori Pref.(JP)

Inventor: Fujii, Katsumasa
1344, Numa
Okayama City Okayama Pref.(JP)


Representative: Rackham, Stephen Neil et al,
GILL JENNINGS & EVERY 53-64 Chancery Lane
London WC2A 1HN(GB)

Breath-synchronized concentrated-oxygen supplier.

Apparatus for supplying oxygen-enriched air to a patient (22) in synchronism with the patient's respiration, includes a regulator (29) controlling the duration for which oxygen enriched air is supplied for each inhalation. The duration is based on a combination of averaging process of the

durations of preceding inhalations and a certain ratio that is set on the regulator (29), so that the air supply to the patient is halted both during a last portion of each inhalation and during exhalation.

FIG.1



BREATH-SYNCHRONIZED CONCENTRATED-OXYGEN SUPPLIER

This invention relates to a breath-synchronized concentrated-oxygen supplier, and more particularly to an apparatus which supplies oxygen-enriched gas to a patient in synchronism with the inhalation phase of his
05 respiration.

With the recent progress in the medical art, an increasing number of oxygen concentrators have been used in inhalation therapy for patients suffering from respiratory ailment or circulatory diseases. Particu-
10 larly, oxygen concentrators for home use have become remarkably popular these days, because they are capable of concentrating the oxygen gas in air by the use of a household electric power source through a simple operation, and supplying such concentrated oxygen gas
15 for medical use. In the United States of America, a standard for the home oxygen concentrator, namely American National Standard Institute (ANSI) Z79. 13, 1981, has been established under the guidance of Federal Food and Drug Administration (FDA). Further, an international
20 standard for it, e.g., International Organization for Standardization ISO 5059, is now ready to be published. In countries where medical treatment at home prevails, such oxygen concentrators are used to eliminate the inconvenience involved in the conventional oxygen

distribution by use of heavy pressure vessels such as gas cylinders.

In general, there are two kinds of methods for treating patients by inhalation of oxygen gas or
05 the like; namely, the so-called "closed circuit method" and the so-called "open circuit method".

The closed circuit method uses a "facemask apparatus" on the face or an endotracheal tube inserted into the trachea of the patient and supplies the gas to
10 the patient through a passage, which is airtightly separated from the atmosphere and extends between the breathing device, i.e., the respirator or the gas supply system, and the patient's respiratory system. This closed circuit method has an advantage in its high
15 inhaling efficiency, because the gas can be inhaled at about the same concentration as that of the gas supplied to the closed passage and the patient's breathing can be assisted or adjusted by regulating the pressure of the gas inside. However, the closed circuit method has
20 a shortcoming in that it may cause irritation or discomfort on the side of the patient because of the covering of his mouth and nose and the direct insertion of foreign substance in his trachea. Accordingly, the closed circuit method has been used mainly for seriously
25 sick and unconscious patients or patients under anesthesia.

On the other hand, the open circuit method uses a breathing passage which is open to the atmosphere.

In this method, the tip of the gas supplying tube is inserted into the nostril or the mouth of the patient so as to feed the gas without using any airtight connection between the apparatus and the face or upper airway of the patient, and the irritation or discomfort on the side of the patient are reduced and the patient is allowed to speak, eat or drink during the inhalation treatment by this method. Accordingly, this open circuit method is mainly used for mild cases in which self-breathing is possible.

In the closed circuit type breathing apparatus, oxygen or gas mixture for inhalation may be supplied in response to the patient's spontaneous breathing by detecting the gas pressure changes in the closed respiratory circuit, because the latter can be used as a triggering mechanism. However, in the conventional open circuit type breathing apparatus, it is difficult to detect the ample pressure change enough to trigger the gas supply in the open respiratory circuit, and in most cases, the gas is supplied at a constant flow rate regardless of the patient's breathing. Accordingly, the gas is forced to the patient even during his exhalation and discomfort has been caused to the patient. Besides, a large part of the constantly fed gas is wasted because the gas supplied during patient's exhalation is discharged to the atmosphere without being used.

Besides, the open circuit type breathing

constant flow rate oxygen insufflation system in clinical practice.

To overcome the shortcomings of the conventional open circuit type breathing system, the Japanese
05 Patent Laying-open Publication No. 8,972/84 proposed a breath-synchronized open circuit type breathing system. In the breath-synchronized type, oxygen gas is supplied only during inhalations of the patient, so that this type breathing system has advantages in that the
10 patient's comfort is ensured during the inhalation treatment and that the oxygen concentrator can be made small due to the reduced use of oxygen.

The oxygen concentrators can be classified into two types, i.e., the so-called membrane type and
15 the so-called molecular adsorption type. The membrane type oxygen concentrator passes the air through a special membrane which transmits oxygen more easily than nitrogen, so that the oxygen concentration is enhanced by increasing the number of oxygen molecules
20 relative to the number of nitrogen molecules. With this membrane type, the maximum attainable oxygen concentration is limited to about 40% at most. Thus, the membrane type concentrator is rather suitable for closed circuit type breathing system in which the
25 oxygen gas is inhaled at about the same concentration as supplied by the oxygen concentrator.

In the molecular adsorption type (also referred to as "pressure swing adsorption" type), the air is

passed through an adsorption cylinder filled with a special substance (adsorbent) while increasing and decreasing the air pressure, and nitrogen and moisture in the air are removed by repeated adsorption and
05 desorption processes so as to produce highly concentrated oxygen. With this type concentrator, an oxygen concentration higher than 90% can be obtained. Thus, the molecular adsorption type concentrator is suitable for long inhalation treatments by using an open circuit
10 type breathing system allowing the mixing of open air with the concentrated oxygen gas for inhalation.

However, the molecular adsorption type has a shortcoming in that when the outflow of the oxygen-enriched gas increases, the amount of purge gas for
15 regenerating the adsorbent decreases, resulting in a gradual reduction of the oxygen concentration of the oxygen-enriched output gas. Such reduction of the oxygen concentration is contrary to the very purpose of the oxygen concentrator. As a countermeasure, it has
20 been tried to use oxygen concentrators of larger size and to improve their technical performance, but there have been certain limits in such trial.

To solve such shortcoming of the molecular adsorption type oxygen concentrator, the Japanese
25 Patent Application Publication No. 5,571/82 corresponding to U.S. Patent No. 4,331,455 proposes an oxygen concentrator using two adsorption cylinders, which cylinders are alternately operated in such a manner that during

the adsorption cycle of one cylinder, a part of the oxygen-enriched output gas from that cylinder is used as the purge gas for the other cylinder. Such oxygen concentrator with the two adsorption cylinders has an
10 advantage in that, even when adsorption cylinders of comparatively small capacity are used, oxygen-enriched gas with a desired concentration can be produced over a long period of time with a high stability because the two cylinders are efficiently purged with each other.

10 The respiration pattern of a human being or the like living body will be briefly reviewed now. The oxygen partial pressure in the arterial blood during the respiration can be effectively increased by providing a sufficiently high peak flow rate of oxygen
15 at the beginning of the inhalation phase. The inhaled gas at the end portion of the inhalation phase does not reach the respiratory organ but fills up the so-called dead space portion, so that it is not used effectively in the respiratory organ. In view of the above characteristics of the respiration pattern, the efficiency of
20 the oxygen-enriched gas usage in terms of its utilization factor can be improved by using such breath-synchronized control in which a sufficiently high peak flow rate of oxygen-enriched gas is superposed onto the initial
25 portion of the steady state flow rate of such gas during the inhalation phase while the oxygen-enriched gas supply is interrupted at a certain end portion of the inhalation phase.

The breath-synchronized open circuit type breathing system disclosed by the above-mentioned Japanese Patent Laying-open Publication No. 8,972/84, however, uses such control that a constant flow rate of the oxygen gas with a certain concentration is maintained during the inhalation phase and the interruption of the oxygen gas supply near the end of the inhalation phase is effected by a one-shot circuit which is actuated at the beginning of the inhalation phase, so that the oxygen is supplied for a predetermined period of time. Thus, with this breathing system, the oxygen partial pressure of the blood may not be raised so effectively and the utilization rate of the oxygen gas may not be sufficiently high. Further, the duration of oxygen gas supply for the inhalation phase is set at a certain value but is not variable in response to the patient's respiration, so that the breathing system cannot respond well to irregularity of the respiration and it may sometimes become out of synchronism with the patient's respiration, resulting in a still lower utilization rate.

The respiration pattern of a human being inherently varies from person to person, and even for one person, the speed and magnitude of the respiration vary depending on circumstances. Even under the same conditions, actual measurements of the durations of individual inhalations and exhalations show dispersions. Ideally, the timing and duration of the oxygen gas

supply from the breathing system should be automatically controlled so as to be in synchronism with each of the ever varying inhalation timing and duration depending on the personal, circumstantial and individual respiratory differences.

05 The oxygen concentrator disclosed in the above-mentioned Japanese Patent Laying-open Publication No. 5,571/82 produces an almost constant flow rate of the oxygen gas with a certain concentration, so that it
10 has shortcomings in that its utilization rate in terms of usage by the living body may be relatively low and that it may still cause irritation and discomfort on the side of patients or the like.

Therefore, an object of the invention is to
15 obviate the above-mentioned difficulties of the prior art by providing a novel breath-synchronized concentrated-oxygen supplier which is capable of increasing the utilization factor of oxygen-enriched gas, minimizing the irritation, respiratory resistance and discomfort
20 on the side of patient or the like living body, and reducing the size, weight and energy consumption of the supplier.

A preferred embodiment of the breath-synchronized concentrated-oxygen supplier according to
25 the present invention uses an oxygen concentrator producing and storing oxygen-enriched gas, and a buffer tank which temporarily stores the oxygen-enriched gas from the oxygen concentrator. A valve is mounted on

the outlet of the buffer tank so as to control the flow of the oxygen-enriched gas from the buffer tank toward the respiratory system of a living body through a path that is open to the atmosphere. Further, a suitable
05 sensor is exposed to respiration of the living body, so as to generate an output signal indicative of inhalation (inspiratory) phase and exhalation (expiratory) phase of the respiration.

To interrupt the oxygen-enriched gas supply
10 at a certain end portion of each inhalation phase, an input means is provided, so that a ratio between the entire length of the inhalation phase and a specific end portion thereof is set by an operator on the input means. The above valve is provided with such a regulator
15 which is adapted to detect duration of each inhalation phase in succession based on the output signal from the sensor and, to open the valve at the beginning of each inhalation phase to keep the valve open for a period equivalent to an average of the preceding inhalation
20 durations minus the portion corresponding to the above ratio set on the input means. Whereby, the oxygen-enriched gas is supplied to the living body during each inhalation phase except the above specific end portion thereof. The above buffer tank acts to make the initial
25 flow rate of the oxygen-enriched gas higher than the steady state flow rate thereof in each inhalation phase.

In another embodiment of the invention, the above-mentioned oxygen concentrator is formed of

0188071

a reservoir tank, at least two compressor-driven adsorption cylinders, and a controller adapted to run at least one of said adsorption cylinders at a time for producing the oxygen-enriched gas for storing in said
05 reservoir while a portion of the oxygen-enriched gas thus produced is blown into remaining adsorption cylinders at rest for purging.

Each of the above compressor-driven adsorption cylinders may consist of an adsorption cylinder and a
10 compressor directly connected thereto.

It is also possible to form the compressor-driven adsorption cylinders by connecting two or more adsorption cylinders to a common compressor through a selective valve. In the case of connecting two adsorption
15 cylinders to one compressor, the selective valve may be a five-way valve adapted to connect one of said adsorption cylinders at a time to both said compressor and said exhaust passage.

In principle, the concentrated-oxygen supplier
20 of the invention uses a combination of an oxygen concentrator and a breath-synchronizing means. To achieve the synchronism between the breath and the oxygen gas supply, the respiration of a living body is detected, for instance by disposing a temperature sensor, preferably
25 a thermocouple, in front of the nostril and monitoring the change in the electromotive force of the thermocouple due to the temperature change of the respiratory air so as to find the inhalation phase by the temperature

reduction during that phase, and a valve is opened in synchronism with the thus detected inhalation phase for starting the supply of the oxygen-enriched gas as the beginning of the inhalation phase.

05 Thus, the oxygen-enriched gas supply is interrupted during the exhalation phase, and this interruption causes the storing of the oxygen-enriched gas in a buffer tank at an elevated pressure. That elevated pressure facilitates the superposition of a
10 pulse-like initial high flow rate onto the steady state flow rate of the oxygen-enriched gas when the above-mentioned valve is opened at the beginning of the inhalation phase. For each inhalation phase of the respiratory cycle, the duration in which the above
15 valve is kept open is determined by a regulator based on a combination of averaged duration of the preceding inhalation phases as determined by the output from the sensor and the ratio set on the input means from the outside. Thus, the oxygen-enriched gas supply is
20 interrupted with such a timing that the oxygen-enriched gas is not supplied at that end portion of the inhalation phase in which the inhaled gas is filled in the dead space without being used.

 For a better understanding of the invention,
25 reference is made to the accompanying drawings, in which:

 Fig. 1 is a diagrammatic illustration of a breath-synchronized concentrated-oxygen supplier according to the present invention;

0188071

Fig. 2 is an electric circuit diagram showing a sequential control circuit for the controller of an oxygen concentrator in the concentrated-oxygen supplier of Fig. 1;

05 Fig. 3 is a block diagram of a regulator for controlling the gas supply through the supplier of Fig. 1;

Fig. 4A and Fig. 4B are graphs which are used in the description of the operation of the supplier of
10 Fig. 1;

Fig. 5 is a flow chart of the operation of the central processing unit CPU in the regulator of Fig. 3;

Fig. 6 is a block diagram of another oxygen
15 concentrator which can be used in the supplier of the invention; and

Fig. 7A, Fig. 7B and Fig. 7C are graphs illustrating the effects produced by the invention.

Throughout different views of the drawings,
20 1, 61 are oxygen concentrators, 2 is a reservoir tank, 3, 4 are absorption cylinders, 5, 7 are air cleaners, 6, 8 are compressors, 9, 10 are one-way valves, 11 is an orifice, 12, 13 are pressure switches, 14, 15 are solenoid-operated release valves, 16 is a silencer,
25 17 is a controller, 18 is a shutout solenoid valve, 19 is a reducing valve, 20 is a bacteria filter, 21 is a flow meter, 22 is a patient, 23 is a buffer tank, 24 is a breath-synchronizing solenoid valve, 25 is

a humidifier, 26 is a nasal cannula, 27 is an oxygen analyzer, 28 is a thermocouple, 29 is a gas-supply regulator, 31, 32 are power source terminals, 33, 34, 35 are relays, 41 is a differential amplifier, 42, 43, 05 44 are operational amplifiers, 45 is a variable resistor, 46 is a low-pass filter, 47 is an A/D converter, 48 is an operational control unit, 49 is a central processing unit (CPU), 50 is a timer, 51, 52, 53, 54 are memories, 55 is an outside input means, 56 is an alarm, 57 is a 10 buzzer, 62 is a five-way solenoid valve, 63 is a sliding valve, 64, 65 are passages, and 66 is a controller means.

Referring to Fig. 1 showing an embodiment of the invention, an oxygen concentrator 1 consists of one 15 reservoir tank 2 and two adsorption cylinders 3 and 4. The adsorption cylinder 3 is connected to a compressor 6 with an air cleaner 5, so that after being treated by the air cleaner 5 for dust removal the air is compressed by the compressor 6 and the compressed air is delivered 20 to the adsorption cylinder 3. Similarly, the other adsorption cylinder 4 is connected to a compressor 8 with an air cleaner 7, so that compressed air from the compressor 8 is delivered to the adsorption cylinder 4. The adsorption cylinders 3 and 4 are connected to the 25 reservoir tank 2 through one-way valves 9 and 10 respectively, and the two cylinders 3 and 4 are also communicated to each other through an orifice 11, so that the oxygen-enriched gas produced by one adsorption cylinder 3 or 4

is fed to the reservoir tank 2 through the corresponding one-way valve 9 or 10 while a part of such gas is directed to the other adsorption cylinder 4 or 3 through the orifice 11 as purge gas.

05 Pressure switches 12 and 13 are mounted on the input side passages of the adsorption cylinders 3 and 4 respectively, while the input sides of the adsorption cylinders 3 and 4 are also connected to a common silencer 16 through solenoid-operated release
10 valves 14 and 15 respectively. The output side of the silencer 16 is open to the atmosphere. A controller 17 is connected to the pressure switches 12, 13 and the release valves 14, 15. The controller 17 responds to signals from the pressure switches 12, 13 so as to
15 control the operations of the compressors 6, 8, which are preferably in linear motor type for generating oxygen-enriched gas therein in an alternate manner. The controller 17 also controls the release valves 14 and 15, so that substances separated from the adsorbent
20 in the adsorption cylinders 3 or 4 by the purge gas are discharged to the atmosphere together with the purge gas through the release valves 14 or 15 and the silencer 16.

 A shutout solenoid valve 18 is mounted on the output side passage of the reservoir tank 2. This valve
25 18 is closed when the concentrated oxygen supplier is at rest while it is kept open when the supplier is in operation, so that the oxygen-enriched gas is stored in the reservoir tank 2 during the rest period of the

concentrated-oxygen supplier. Whereby, the reservoir tank 2 is kept ready for immediate operation when the supplier is restarted. The pressure of the oxygen-enriched gas delivered through the shutout solenoid valve 18 is reduced to a proper level for inhalation treatment by a reducing valve 19, and the gas is purified by a bacteria filter 20 and its flow rate is adjusted at a level suitable for a patient 22 by a flow meter 21 having a needle valve type adjusting mechanism. The gas is then applied to a buffer tank 23, and a breath-synchronizing solenoid valve 24 controls the gas stream from the buffer tank 23 to a patient 22 through a humidifier 25 and a nasal cannula 26. The humidifier 25 gives a proper humidity to the oxygen-enriched gas so as to make it suitable for inhalation treatment of the patient 22.

An oxygen analyzer 27 may be provides at a suitable position between the shutout solenoid valve 18 and the breath-synchronizing solenoid valve 24, so as to facilitate the detection of any malfunction of the oxygen concentrator 1, especially abnormality of the adsorbent, by operators such as medical doctors and nurses. In the illustrated embodiment, the oxygen analyzer 27 is provided between the bacteria filter 20 and the flow meter 21 as shown in Fig. 1.

As a sensor to detect the exhalation phase of the respiration of the patient 22, this embodiment uses a thermocouple 28 mounted on the nasal cannula 26 in

such a manner that the thermocouple 28 is exposed to the respiratory air flow through the patient's nostril. The output from the thermocouple 28 is applied to a gas-supply regulator 29 which controls the operation of the breath-synchronizing solenoid valve 24 based on the information from the thermocouple 28.

Fig. 2 shows a sequential circuit diagram of the controller 17 of Fig. 1. Each of the pressure switches 12 and 13 has three terminals; namely, a common contact COM connected to a fixed end of a swingable blade 12a or 13a, and two terminals H and L with which the free end of the swingable blade 12a or 13a selectively comes in contact. In the illustrated embodiment, when the pressure in the corresponding adsorption cylinder 3 (4) is equal to or higher than a predetermined value, the swingable blade 12a (13a) is kept in contact with the terminal H, while the swingable blade 12a (13a) is kept in contact with the terminal L as long as the above pressure is below the above predetermined value. The terminal COM of the pressure switch 12 is connected to one power source terminal 31 while the terminal COM of the pressure switch 13 is connected to another power source terminal 32. The power source terminals 31 and 32 are connected to a suitable control power source (not shown).

A relay 33 is provided between the terminal H of the pressure switch 12 and the terminal L of the other pressure switch 13. The relay 33 has two normally open

relay contacts 33-1 and 33-3 and one normally closed relay contact 33-2. The normally open relay contact 33-1 is connected between the relay 33 and the power source terminal 31 as a self-hold contact for the relay 33.

- 05 The normally closed relay contact 33-2 is serially connected to a relay 34, and the serial circuit of the relay contact 33-2 and the relay 34 is connected across the power source terminals 31 and 32. The normally open relay contact 33-3 is serially connected to a
- 10 relay 35, and the serial circuit of the relay contact 33-3 and the relay 35 is also connected across the power source terminals 31 and 32.

The relay 34 has a normally open relay contact 34-1, which contact is connected between one power source

15 terminal 31 and one joint of a parallel combination of the compressor 6 and the solenoid-operated release valve 15, the parallel combination having its opposite joint connected to the other power source terminal 32. The relay 35 has a normally open relay contact 35-1,

20 which contact is connected between one power source terminal 31 and one joint of a parallel combination of the compressor 8 and the solenoid-operated release valve 14, the parallel combination having its opposite joint connected to the other power source terminal 32.

- 25 Fig. 3 shows the electric circuit of the gas-supply regulator 29 of Fig. 1. The output from the thermocouple 28 acting as a sensor of respiration is applied to a differential amplifier 41 of the

regulator 29. Operational amplifiers 42 and 43 of the differential amplifier 41 amplify the input from the thermocouple 28 and apply their output to an output stage operational amplifier 44 having a variable resistor 45 for gain adjustment. The output from the operational amplifier 44 is applied to a low-pass filter 46 for eliminating high-frequency noise and then converted into digital signals by an A/D converter 47, which digital signals are applied to an operational control unit 48. The control unit 48 has a central processing unit (CPU) 49, a timer 50, and memories 51 through 54. The CPU 49 is connected to an outside input means 55, such as a keyboard, through which means a ratio between the duration of an inhalation phase and the length of a specific end portion thereof is applied to the CPU 49 as an input information.

Preferably, the gas-supply regulator 29 has a fool-proof mechanism; namely, the above-mentioned ratio of a desired magnitude can be accepted only when it falls within a certain predetermined range, lest a wild input at the outside input means 55 by a mistake should cause a total stop of the oxygen-enriched gas supply.

The timer 50 has three functions; namely, a function of applying interruption signals to the CPU 49 for sampling the output from the A/D converter 47 at certain intervals, e.g., at every 10 msec in the illustrated embodiment, a function of measuring the open time of the breath-synchronizing solenoid valve 24

in the inhalation phase, and a function of measuring the duration of individual inhalation phases and exhalation phases. The memory 51 stores the data of preceding sampling, which sampling is effected in succession in a
05 cyclic manner by the CPU 49. The memory 52 stores flags for identifying the inhalation phase and the exhalation phase, e.g., a bit "1" for the inhalation phase and a bit "0" for the exhalation phase as in the case of the illustrated embodiment. The memory 53
10 stores time data on inhalation phases of the immediately preceding six normal respiratory motions while updating them. The memory 54 stores a program for controlling the operational control unit 48.

The CPU 49 of the illustrated embodiment
15 carries out the operations as instructed by the program from the memory 54 based on the data from the A/D converter 47, the time data on the past six normal inhalation phases as stored in the memory 53, and the data from the outside input means 55, so that control
20 signals for the breath-synchronizing solenoid valve 24 are dispatched from the CPU 49 as a result of such operations. When an alarm 56 for indicating irregularity of the patient's respiration and a buzzer 57 for indicating the normal operation of the concentrated-oxygen
25 supplier are provided, the CPU 49 also controls the operations of such alarm 56 and the buzzer 57.

The operation will be described now. The operation of the oxygen concentrator 1 will be explained at

0188071

first by referring to Fig. 1 and Fig. 2. When the concentrator 1 is started without high pressure in the adsorption cylinders 3 and 4, the swingable blades 12a and 13a of the pressure switches 12 and 13 are kept on their L contacts, so that the relay 34 is energized. Accordingly, the normally open relay contact 34-1 is closed, and the compressor 6 is started and the solenoid-operated release valve 15 is actuated so as to open the passage from the adsorption cylinder 4 to the atmosphere through the silencer 16. Thus, the air purified by the air cleaner 5 and compressed by the compressor 6 is delivered into the adsorption cylinder 3, and nitrogen in the air thus delivered is adsorbed by the adsorbent filled in the cylinder 3 so as to increase the oxygen concentration of the air, and the oxygen-enriched gas from the cylinder 3 is stored in the reservoir tank 2 through the one-way valve 9.

At the same time, a part of the oxygen-enriched gas is delivered to the other adsorption cylinder 4 through the orifice 11 as the purge gas, so that nitrogen and moisture carried by the adsorbent in the cylinder 4 are released by the purge gas and discharged to the atmosphere through the now open release valve 15 and the silencer 16. Whereby, the ability of the adsorbent in the cylinder 4 is regenerated and revived.

In response to the operation of the compressor 6, the inside pressure of the adsorption cylinder 3 increases. When that inside pressure reaches a certain

value, the swingable blade 12a of the pressure switch 12 is turned to the terminal H, so that the relay 33 is energized. Accordingly its normally open relay contact 33-1 is closed to complete the self-hold circuit of the

05 relay 33, and the energization of the relay 33 is maintained by its own relay contact 33-1 even when the inside pressure of the adsorption cylinder 3 decreases and the swingable blade 12a of the pressure switch 12 is turned to the terminal L. Upon energization of the

10 relay 33, its normally closed relay contact 33-2 is opened and its normally open relay contact 33-3 is closed, so that the relay 34 is de-energized and the relay 35 is energized. The de-energization of the relay 34 causes the relay contact 34-1 to open, and the

15 compressor 6 comes to rest and the solenoid-operated release valve 15 is turned off and closed.

On the other hand, when the relay 35 is energized, its normally open relay contact 35-1 is closed, so as to start the compressor 8 and turn on the

20 solenoid-operated release valve 14 for opening the passage from the adsorption cylinder 3 to the silencer 16. Thus, the gas in the adsorption cylinder 3 can be discharged to the atmosphere through the release valve 14 and the silencer 16, so as to facilitate the desorption

25 of nitrogen and moisture adsorbed in the adsorbent in the cylinder 3. After the compressor 8 is started, the air cleansed by the air cleaner 7 and compressed by the compressor 8 is delivered through the adsorption

cylinder 4 to the reservoir tank 2 as the oxygen-enriched gas through the one-way valve 10. A part of the oxygen-enriched gas from the cylinder 4 is also applied to the other cylinder 3 through the orifice 11 as the purge
05 gas, so as to regenerate and reactivate the adsorbent in the cylinder 3 in the manner described above.

When the inside pressure of the adsorption cylinder 4 increases and reaches a certain value, the swingable blade 13a of the pressure switch 13 mounted
10 on the input side of the adsorption cylinder 4 is turned to its terminal H, so as to de-energized the relay 33 in the circuit of Fig. 2. Hence, the relay 35 is de-energized and the relay 34 is energized again. Thus, the conditions of the control circuit of Fig. 2
15 come back to that at the beginning of the operation of the oxygen concentrator 1, and one cycle of the alternating operations of the adsorption cylinders 3 and 4 is completed. Thereafter, the above-described operation will be repeated in a cyclic manner, and the oxygen-
20 enriched gas will be stored in the reservoir tank 2.

It is noted here that the oxygen concentrator 1 of the illustrated embodiment is adapted to ensure quick buildup of a sufficiently high oxygen concentration upon its start even if its preceding operation is
25 ceased at an arbitrary time. More particularly, the actual control circuit of the oxygen concentrator 1 is such that even after the turning off of its start-stop switch, the above-described operation including the

supply of the purge gas is maintained until the regeneration of the adsorbents in both of the adsorption cylinders 3 and 4 is completed, and upon completion of such regeneration, the operation is automatically brought to rest. Besides, in order to prevent the deterioration of the adsorbent due to its contact with the moisture of the open air when the oxygen concentrator 1 is not used, the adsorption cylinders 3 and 4 and the associated pipings in the embodiment of Fig. 1 are airtightly sealed from the open air when the concentrator 1 is not used for any extended period of time.

The operation of the gas-supply regulator 29 will be described now. Fig. 4A shows the waveform of the output voltage from the thermocouple 28 as seen at the input side of the A/D converter 47 after the amplification at the differential amplifier 41 and the noise elimination at the low-pass filter 46. Since the thermocouple 28 is exposed to the respiratory air passing the patient's nostril, its output voltage gradually increases during the exhalation phase in which the air is exhaled from the inside of the patient's body while its output gradually decreases during the inhalation phase. Thus, the output voltage of the thermocouple 28 is approximately sinusoidal.

The A/D converter 47 converts the output of the thermocouple 28 into digital signals in the following manner. The CPU 49 samples the voltage of Fig. 4A at a regular interval of 10 msec in response

to the interruption signal from the timer 50 and the sampled value is stored in the memory 51 as a temperature datum, and the CPU 49 compares the latest temperature as sampled against the preceding temperature datum
05 retrieved from the memory 51. If the latest temperature as sampled is higher than the preceding temperature datum, the respiration is in the exhalation phase wherein the output voltage of the thermocouple 28 gradually increases as shown in Fig. 4A. On the other
10 hand, if the latest temperature as sampled is lower than the preceding temperature datum, the respiration is in the inhalation phase wherein the output voltage of the thermocouple 28 gradually decreases as also shown in Fig. 4A. To identify the durations of the
15 exhalation and inhalation phases, a binary flag "1" for exhalation and a binary flag "0" for inhalation are stored in the memory 52 during the respective phases.

Let it be assumed that, at a certain instant, the memory 52 carries a binary flag "1" indicating that
20 the respiration is in the exhalation phase. During the exhalation phase, the temperature datum stored in the memory 51 is renewed by the latest sampled temperature only when such latest temperature as sampled from the A/D converter 47 is higher than the preceding temperature
25 datum retrieved from the memory 51. If the latest temperature as sampled is lower than the preceding temperature datum retrieved from the memory 51, i.e., at the transit from the exhalation phase to the inhalation

phase, the binary flag in the memory 52 is changed to "0" and the latest lower temperature as sampled is stored in the memory 51 as a new datum. At the same time, the breath-synchronizing solenoid valve 24 is
05 turned on for opening the passage to the nasal cannula 26, and the supply of oxygen-enriched gas to the patient 22 starts while the buzzer 57 starts to sound. Thereafter, during the inhalation phase, as long as the newly sampled temperature is lower than the preceding temperature datum, such newly sampled temperature is stored
10 in the memory 51 for renewing the temperature datum therein.

Both the duration of the inhalation phase from the exhalation-inhalation transit to the inhalation-
15 exhalation transit and the duration of the exhalation phase from the inhalation-exhalation transit to the exhalation-inhalation transit are measured by a combination of the CPU 49 and the timer 50. Whether each of the thus measured durations falls in a normal range or
20 not is checked by a program stored in the memory 54. In the illustrated embodiment, the normal range of the duration of both the inhalation and exhalation phases is assumed to be 1-15 seconds. When durations of the inhalation and exhalation phases are normal, data on
25 the immediately preceding six consecutive sound inhalation durations are stored in the memory 53 while renewing them in succession.

On the other hand, if any of the inhalation

05 durations and exhalation durations falls outside the above normal range, it is assumed that abnormality of a kind has occurred on the side of the patient 22 or the thermocouple 28. Such abnormality is informed to doctors and nurses by actuating the alarm 56 by the CPU 49. At the same time, the breath-synchronizing solenoid valve 24 is controlled in such a manner that the oxygen-enriched gas is continuously supplied to the patient 22. The renewal of the data on the preceding
10 six consecutive sound inhalation durations is effected when a new inhalation duration datum of the latest sound respiratory cycle is made available by erasing the oldest (seven respiratory cycles before) datum and storing such new inhalation duration datum.

15 When the respiratory cycles are sound, the oxygen-enriched gas is supplied only in the inhalation phase. The duration of such supply, namely, the duration of the opening of the breath-synchronizing solenoid valve 24 (to be referred to as the "valve open time"),
20 is controlled by a combination of a time ratio set on the outside input means 55 and the average of the preceding six consecutive sound inhalation durations. More particularly, at the transit from the exhalation phase to the inhalation phase, data on the immediately
25 preceding six consecutive sound inhalation durations are read from the memory 53 for determining the average value thereof. A product of that average value of the inhalation durations and the time ratio set on the

outside input means 55 is calculated. The valve open time is determined by subtracting the above product from the above average value of the six inhalation durations.

05 That valve open time is set on the timer 50, and as the oxygen-enriched gas is supplied it is counted down, so that when the thus set time is reduced to zero by the counting down the breath-synchronizing solenoid valve 24 is closed. Thus, the valve open time for the
10 breath-synchronizing solenoid valve 24 for a specific inhalation phase is shorter than the average value of the immediately preceding six consecutive inhalation durations by the time ratio set on the outside input means 55, as shown in Fig. 4B. The gas to be filled in
15 the trachea or other dead space of the patient 22 is provided by the atmospheric air inhaled by him during the time corresponding to the above time ratio.

 If the actual duration of an inhalation phase is shorter than the valve open time set on the timer 50
20 for that inhalation phase, the CPU detects the transit from the inhalation to exhalation based on the temperature data during the above counting down at the timer 50, and the flag in the memory 52 is changed from "0" to "1". Thus, in this case the breath-synchronizing
25 solenoid valve 24 is closed before the valve open time is counted to zero at the timer 50.

Fig. 5 shows a flow chart of the operation of the CPU 49 in response to the interruption signals from

the timer 50 at 10 msec intervals. The operation of the CPU will be summarized now. When the operation of the gas-supply regulator 29 is started, the temperature variation of the respiratory air of the patient or the
05 like living body is monitored as a pattern. In this embodiment, the breath-synchronizing solenoid valve 24 is kept open at first unit six consecutive sound inhalation duration data are stored in the memory 53, so that the oxygen-enriched gas is continuously supplied
10 to the patient's respiratory organ during such initial period. In each inhalation phase after data on the six consecutive sound inhalation durations are stored in the memory 53, the valve open time for that inhalation phase is determined based on the average of the thus
15 stored data in the memory 53 and the time ratio set on the outside input means 55, and the breath-synchronizing solenoid valve 24 is turned on from the start of that inhalation phase for the period of the thus determined valve open time so as to supply the oxygen-enriched gas
20 to the respiratory organ of the patient 22 or the like living body.

As long as the sound respiratory pattern is maintained, the inhalation duration data older than six respiratory cycles before the present instant are
25 erased from the memory 53, so as to ensure the derivation of the average of the latest six consecutive sound inhalation durations. When the duration of inhalation or exhalation phase falls outside of a normal duration

range (to be separately set), the breath-synchronizing solenoid valve 24 is immediately turned on so as to continuously supply the oxygen-enriched gas to the patient or the like, and at the same time the alarm 56
05 is actuated. When the sound respiration is resumed thereafter and conditions for normal operation are met, the breath-synchronized operation is resumed and the alarm 56 is turned off. However, unless the sound respiration is resumed, the continuous supply of the
10 oxygen-enriched gas is maintained and the alarm 56 is continuously actuated.

In the above example, the valve open time of the breath-synchronizing solenoid valve 24 is determined based on the preceding six consecutive inhalation
15 durations. However, the invention is not restricted to such preceding six inhalation durations, and an average of an arbitrary number of the preceding inhalation durations can be used for determining the valve open time. As another modification, the valve open time may
20 be determined by taking a product of the duration of the immediately preceding inhalation phase and the time ratio set on the outside input means 55 and by subtracting such product from the duration of the immediately preceding inhalation phase. Further, the valve open
25 time for a following inhalation phase may be determined by taking the average of such a calculated time determined based on the immediately preceding inhalation duration and more preceding valve open times. That is,

0188071

the valve open time for the next inhalation phase is determined by an average of the preceding valve open time and the present inhalation duration so measured minus a product of it and the ratio set on the outside
05 input means.

Fig. 6 shows another embodiment of the oxygen concentrator to be used in the concentrated-oxygen supplier of the invention. The oxygen concentrator 61 of this embodiment uses one compressor 6 which is
10 alternately connected to two adsorption cylinders 3 and 4 through a five-way solenoid valve 62. The formation of the oxygen concentrator 61 is similar to that of the oxygen concentrator 1 of Fig. 1 except the above five-way solenoid valve 62 and the use of only one compressor 6.
15 Like parts are designated by like numerals. The five-way solenoid valve 62 has a sliding valve 63 which can selectively assume a first position as shown in Fig. 6 and a second position to the left thereof. At the first position, the valve 63 connects the compressor 6
20 to the adsorption cylinder 3 through a passage 64 while connecting the adsorption cylinder 4 to the silencer 16 through another passage 65. The valve 63 located at the second position connects the compressor 6 to the adsorption cylinder 4 through the passage 65 while
25 connecting the adsorption cylinder 3 to the silencer 16 through the passage 64.

A controller means 66 shifts the valve 63 between the first position and the second position in

- 32 -

response to the output from the pressure switch 12. More particularly, when the compressor 6 operates with the valve 63 at the position 1 as shown in Fig. 6, the air cleansed by the air cleaner 5 and compressed by the compressor 6 enters the adsorption cylinder 3 through the passage 64, so as to produce oxygen-enriched gas. As in the case of Fig. 1, the thus produced oxygen-enriched gas is stored in the reservoir tank 2 through the one-way valve 9, and at the same time a part of the oxygen-enriched gas is delivered to the other adsorption cylinder 4 through the orifice 11 as purge gas. The purge gas causes desorption of nitrogen and moisture from the adsorbent in the adsorption cylinder 4, and the desorption products are discharged to the atmosphere together with the purge gas through the passage 65 and the silencer 16.

When the inside pressure of the adsorption cylinder 3 increases and reaches a certain predetermined value, the pressure switch 12 generates and transmits such a signal to the controller means 66 that the sliding valve 63 is shifted from the position 1 to the left as seen in Fig. 6 until reaching its second position. Whereby, the gas in the adsorption cylinder 3 is discharged to the atmosphere together with desorbed nitrogen and moisture through the passage 64 and the silencer 16. At the same time, the air cleansed by the air cleaner 5 and compressed by the compressor 6 enters the adsorption cylinder 4 through the passage 65 for

producing the oxygen-enriched gas. The thus produced oxygen-enriched gas is stored in the reservoir tank 2 through the one-way valve 10, while a part of the oxygen-enriched gas is delivered to the adsorption
05 cylinder 3 through the orifice 11 as the purge gas for effecting the regeneration and reactivation of the adsorbent therein.

Thereafter, when the inside pressure of the adsorption cylinder 4 increases and reaches the above-
10 mentioned certain predetermined value, the controller means 66 shifts the valve 63 of the five-way valve 62 to the first position as shown in Fig. 6. Whereby, the oxygen concentrator comes back to the initial condition and one cycle of the operation of the oxygen concentrator
15 of Fig. 6 is completed.

Accordingly, when the five-way valve 62 is used, one compressor 6 can alternately pressurize and purge the two adsorption cylinders as in the case of Fig. 1 using two compressors. It should be noted that
20 the oxygen concentrator to be used in the concentrated-oxygen supplier of the invention is not restricted to the above adsorption type, but membrane type oxygen concentrator can be also used in the present invention.

As described in the foregoing, the breath-
25 synchronized concentrated-oxygen supplier of the invention uses a combination of an oxygen concentrator, a buffer tank, a breath-synchronizing solenoid valve, and a gas-supply regulator which limits the opening

time of the above solenoid valve only to a period available for useful usage of the oxygen gas, so that the following outstanding effects can be achieved.

- (a) Table 2 shows the result of tests on the change of oxygen concentration of the oxygen-enriched gas in breathing apparatuses for two cases both using the same adsorption type oxygen concentrator; namely, a case of the breath-synchronized type of the invention and another case of a conventional continuous type.

Table 2 Oxygen Concentration
and Supply Method

Flow Rate (l/min)	Oxygen Concentration (%)	
	Continuous supply	Breath- synchronized supply
1	94	94
2	90	94
3	76	90
4	58	86
5	50	80

As can be seen from Table 2, the breath-synchronized type supply according to the invention, which supplies the oxygen gas only during the inhalation phase, improves the performance and inhalation efficiency of the supplier to a great extend in

comparison with the conventional continuous supply type. If breathing apparatuses of the breath-synchronized supply type and the continuous supply type are made to obtain the same inhalation efficiency by using the same oxygen concentrator, the breath-synchronized supply type can be made much smaller in size, lighter in weight, and more energy saving than the continuous supply type. Accordingly, the concentrated-oxygen supplier of the invention makes an epoch-making progress in the art and makes the oxygen inhalation treatment at home more readily available.

(b) A buffer tank is provided upstream of the breath-synchronizing solenoid valve, so that the pressure in the buffer tank is raised during the exhalation phase wherein the supply of oxygen-enriched gas is halted, as shown in Fig. 7A. The discharge of such raised pressure at the beginning of the inhalation phase results in a sufficiently high peak-like initial flow rate of the oxygen-enriched gas which is superposed on the steady flow rate in each inhalation phase, as shown in Fig. 7B. Such peak-like initial high flow rate matches the steep change in the respiratory flow curve from the end of exhalation phase to the very beginning of the inhalation phase in the respiration of the living body, as shown in Fig. 7C. Thus, the superposition of the above initial peak of the oxygen flow rate

suits the respiratory pattern of the living body very well.

Oxygen inhalation efficiency in the living body was tested with four models of inhalation; namely, a model (1) with inhalation of air, a model (2) with a continuous supply of oxygen-enriched gas at 2 l/min from an oxygen concentrator, a model (3) with a supply of oxygen-enriched gas at 2 l/min only for inhalation phases from an oxygen concentrator through a three-way valve which discharged the oxygen-enriched gas to the atmosphere during exhalation phases, and a model (4) with a supply of oxygen-enriched gas at 2 l/min only for inhalation phases from an oxygen concentrator through a two-way valve which stored the oxygen-enriched gas in a buffer tank during exhalation phases. The result is shown in Table 3.

Table 3 Transcutaneous Tissue Oxygen Partial Pressure in Living Body for Different Inhaling Models

Model	Transcutaneous Tissue O ₂ Partial Pressure (tcPO ₂) (mmHg)
(1)	73.1 ± 5.4
(2)	122.7 ± 10.5
(3)	105.5 ± 15.3
(4)	163.1 ± 12.6

Similarly, oxygen inhalation efficiency in the living body was tested for different flow rates of inhaling oxygen gas under different gas supplying conditions; namely, condition (i) under continuous oxygen gas supply, condition (ii) under intermittent oxygen gas supply with a 100 ml buffer tank, condition (iii) under intermittent oxygen gas supply with a 200 ml buffer tank, and condition (iv) under intermittent oxygen gas supply with a 400 ml buffer tank. The result is shown in Table 4.

Table 4 Transcutaneous Oxygen Partial Pressure in Living Body for Different Gas Supply Rates

Supply Condi- tions	Transcutaneous Tissue O ₂ Partial Pressure (tcPO ₂) (mmHg)			
	Oxygen Flow Rate (l/min)			
	0.5	1.0	2.0	3.0
(i)	89.9±3.4	93.1±4.5	129.7±13.9	145.2±5.8
(ii)	101.3±4.6	109.7±6.5	173.4±18.1	193.9±17.5
(iii)	101.8±3.5	112.5±12.3	175.2±18.6	191.7±15.6
(iv)	102.6±3.1	108.4±4.0	173.1±12.2	191.1±20.8

As can be seen from the test results of Table 3 and Table 4, with the intermittent supply of oxygen, the oxygen-enriched gas can be inhaled at a very high efficiency. Especially, the model (4) of Table 3 shows that the use of the buffer tank, the

capacity of which as small as 100 ml is shown to be effective enough in Table 4, improves the effectiveness of the breath-synchronized concentrated-oxygen supply system to a greater extent.

- 05 (c) Since the duration of the supply of the oxygen-enriched gas for each inhalation phase is controlled by a combination of the preceding inhalation durations and the time ratio of a specific end portion of the inhalation duration as set through
10 an outside input means, the oxygen-enriched gas can be supplied in excellent synchronism with the respiration of the patient or the like, so that the efficiency of the oxygen gas supply can be further improved. In view of the high inhalation
15 efficiency thanks to the use of the buffer tank, the time ratio indicating the length of the specific end portion of the inhalation duration, in which end portion the gas supply is interrupted, can be made comparatively large.
- 20 Thus, the invention facilitates further miniaturization, weight reduction and energy saving in the oxygen concentrator.

- (d) The oxygen concentrator in the illustrated embodiment of the invention uses two adsorption cylinders
25 which are operated alternately in such a manner that a part of the oxygen-enriched gas produced by one adsorption cylinder and saved by closing the breath-synchronizing valve is delivered to the

other adsorption cylinder as purge gas, so that the oxygen concentrator can operate at a fairly high flow rate of the oxygen-enriched gas without reducing the oxygen concentration therein.

05 Accordingly, the performance of such oxygen concentrator can be considerably improved as compared with conventional oxygen concentrators. The improved performance facilitates further miniaturation, weight reduction and energy saving in the oxygen
10 concentrator.

The interruption of the supply of the oxygen-enriched gas during exhalation phases contributes to speeding up of the pressure buildup at the adsorption cylinders and quickening of the switching
15 of the alternate operations of the adsorption cylinders. The effect of such quickened switching will be positively combined with the above-mentioned effect of the alternate operation of two adsorption cylinders in improving the performance of the
20 oxygen concentrator.

(f) The thermocouple used in the above embodiment for sensing the patient's respiration produces signals which accurately follow the respiration and facilitates accurate control. The thermocouple as
25 the respiration sensor can be made small and light so as to eliminate the resistance to respiration and to reduce the patient's uneasy feeling, and such sensor with stable performance can be manufactured

at a low cost on a mass production basis. In fact, it may be discarded after each inhalation treatment.

- (g) The buzzer used in the above embodiment sounds in synchronism with the operation of the breath-synchronizing solenoid valve, so as to inform the patient of the orderly operation of the breathing apparatus. Whereby, the patient becomes confident with the reliable operation of the apparatus. Besides, such buzzer can be used for training the patient in learning a proper respiratory rhythm suitable to him, which training is useful in rehabilitation from chronic respiratory ailment.
- (h) When a membrane type oxygen concentrator is used, the service life of the selectively permeable membrane therein can be improved by minimizing the oxygen production through suppression of wasteful use of oxygen.

Although the invention has been described with a certain degree of particularity, it is understood that the present disclosure has been made only by way of example and that numerous changes in details of construction and the combination and arrangement of parts may be resorted to without departing from the scope of the invention as hereinafter claimed.

CLAIMS

1. A breath-synchronized concentrated-oxygen supplier, comprising

an oxygen concentrator producing and storing oxygen-enriched gas;

a buffer tank temporarily storing the oxygen-enriched gas from the oxygen concentrator;

a valve mounted on an outlet of said buffer tank so as to control flow of the oxygen-enriched gas from the buffer tank to a respiratory system of a living body through a path that is open to the atmosphere;

a sensor exposed to respiration of the living body and adapted to generate an output signal indicative of inhalation phase and exhalation phase of the respiration;

an input means on which a ratio between entire length of the inhalation phase and a specific end portion thereof is set; and

a regulator adapted to detect duration of each inhalation phase in succession based on the output signal from said sensor and to open said valve at the beginning of each inhalation phase, as well as to determine the open time based on a period equivalent to a combination of averaging of the preceding inhalation durations and said ratio set on the input means; whereby oxygen-enriched gas is supplied to said living body during each inhalation phase except said specific end portion thereof, and said buffer tank acts to make

initial flow rate of the oxygen-enriched gas higher than steady flow rate thereof in each inhalation phase.

2. A breath-synchronized concentrated-oxygen supplier as set forth in claim 1, wherein said oxygen concentrator has a reservoir tank, at least two compressor-driven adsorption cylinders, and a controller adapted to run at least one of said adsorption cylinders at a time for producing the oxygen-enriched gas for storing in said reservoir while a portion of the oxygen-enriched gas thus produced is blown into remaining adsorption cylinders at rest for purging.

3. A breath-synchronized concentrated-oxygen supplier as set forth in claim 2, wherein each of said compressor-driven adsorption cylinders has an adsorption cylinder and a compressor directly connected thereto.

4. A breath-synchronized concentrated-oxygen supplier as set forth in claim 2, wherein said compressor-driven adsorption cylinders consist of one compressor, one exhaust passage, two adsorption cylinders, and a five-way valve adapted to connect one of said adsorption cylinders at a time to both said compressor and said exhaust passage.

1/6

FIG. 1




FIG. 2





FIG. 3



3/6

FIG. 4A






FIG. 4B




4/6

FIG. 5



5/6

FIG. 6



European Patent
Office

EUROPEAN SEARCH REPORT

0188071
Application number

DOCUMENTS CONSIDERED TO BE RELEVANT			EP 85308311.1
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl. 4)
A	US - A - 4 484 578 (G. DURKAN) * Totality; especially claims 1,5 * --	1	A 61 M 16/00
A	US - A - 3 961 627 (H. ERNST et al.) * Totality; especially claims 1-3 * --	1	
A	US - A - 4 106 503 (R.R.ROSENTHAL et al.) * Totality * --	1	
A	GB - A - 1 467 288 (BENDIX CORP.) * Totality * --	1	
D,A	US - A - 4 331 455 (T. SATO) * Totality * D & JP-A2-57-5571 --	1	<div>TECHNICAL FIELDS SEARCHED (Int. Cl. 4)</div> A 61 M 16/00
A	US - A - 4 241 732 (CH. BERNDTSON) * Totality * --	1	
D,A	JP - A2 - 59-8972 (SATOU NABORU) * Totality * ----	1	
The present search report has been drawn up for all claims			
Place of search VIENNA		Date of completion of the search 16-04-1986	Examiner LUDWIG

CATEGORY OF CITED DOCUMENTS

X : particularly relevant if taken alone
Y : particularly relevant if combined with another document of the same category
A : technological background
O : non-written disclosure
P : intermediate document

T : theory or principle underlying the invention
E : earlier patent document, but published on, or after the filing date
D : document cited in the application
L : document cited for other reasons
& : member of the same patent family, corresponding